

PA SPECS MAIN HALL VICTORIE ALKMAAR v2024

STAGE

Permanent stage 16,5m x 8m x 1,2m
Including 2,75mx8m wing on each side, usable stage 11m x 8m
Clearance to first fixture 5,5m
Backdrops can be flown in LX5, maximum 10m wide
Risers available per request

POWER

1x 125A CEE form light SR
2x 32A CEE form audio SL
1x 32A CEE form audio SR
Backline power: 220V or 16A CEE form
(CEE-form is 3 fase + neutral + earth)
Excluding house sound & light power

INFRA

6x Cat5E from FOH to SL
4x MAD1 from FOH to SL
1x LK37 with 12x AES from FOH to SL
Excluding house infra

STANDARD PA SPECS

9x Clair Bros i212 per side powered by Lab Gruppen D 120:4
8x Clair bros CS218 sub powered by Lab Gruppen D 120:4
2x Clair bros Kit12 self powered frontfill
Lake LM44 speaker management (L+R+S+F analog or AES possible on SL)

FOH

Allen & Heath S5000
1x DM48 (48 in / 24 out + 4 AES in / 6 AES out)
1x Dante 64x64 card
1x shout from FOH to MON with Behringer B205D

MONITORS

Allen & Heath S5000
1x DM48 (48 in / 24 out + 4 AES in / 6 AES out)
1x Dante 64x64 card
13x Clair bros 1.5 am+ coaxial stage monitor (including PFL)
2x Clair bros Kit-sub
1x shout from MON to FOH with Behringer B205D

MICROPHONES

2x Shure B91
2x Shure B52
10x Shure SM58
10x Shure SM57
2x Shure B57
12x Sennheiser E904
2x Sennheiser E906

4x Sennheiser MD421
2x Shure B56A
1x Sennheiser MD441
1x Electro Voice RE20
1x AKG D112
2x AKG C414 XL2
4x Neumann KM184
1x Neumann KMS105
12x Klark Teknik DN100

SOUND LIMIT

Max sound level 103 dBa Leq15 / 120dBc Leq15 as by Dutch law
Please note: limiters will be inserted on outputs if this level is exceeded

CONTACT FOR TECHNICAL INQUIRIES

techniek@podiumvictorie.nl